

SELF ADHESIVE GISCOFORM

1. Description

Self adhesive Giscoform consists of a 230 mm. uncured EPDM membrane factory laminated to an autoadhesive butyl Tape. The strip is designed to flash inside and outside corners, pipes, penetrations and other applications as specified in the GISCOSA specifications and details.

2. Propiedades

- Easy and quick instalation
- Reticulum once applied
- Excellent adaptability

3. Application

On cloudy days with ambient temperature below 15°C, the use of a heat gun is recommended to warm the Giscoform, and to ensure good formability. On sunny days, pre-heating of the products is usually not necessary Giscoform Flash is to be applied as per the GISCOSA specifications and details.

4. Coverage

In accordance with length of detail

5. Characteristics

| Technical | EPDM | Autoathesive Tape |
|--------------|---------|-------------------|
| · Base | EPDM | Butyl |
| · Colour | Black | Black |
| · Solvents | None | None |
| · Solids (%) | 100 | 100 |
| · State | Uncured | Uncured |

6. Packaging / Storage / Shelf Life

Packaging: 30,5 m rolls / 1 roll per carton

Storage: Store in original, unopened containers at temperatures between 15°C and 25°C. Keep the material out of direct sunlight until ready for application.

Shelf Life: 12 months, when stored in the above mentioned conditions. Shelf life will be reduced if exposed to higher temperatures.

7. Precautions

Refer to Material Safety Data Sheets.