

GISCOTAPE

1. Description:

The Giscotape membrane is a waterproofing vulcanised EPDM rubber sheet, for all kinds of waterproofing applications in which a 0.4 mm thick and 7.5 cm wide joint has been laminated on both edges and sides to facilitate the joint on site, without needing a primer coat.

2. Properties

- Easy and fast to join, without needing a primer coat.
- Permanent elasticity from -45°C to 130°C.
- Ozone and UV radiation resistance.
- Excellent thermal and dimensional stability.

3. Application

The waterproofing system with Giscotape sheets should be installed by experienced personnel and approved installers, in accordance with the Giscosa Technical Manual, and using the system's accessories.

The area to be waterproofed must be in the normal conditions to carry out a waterproofing job. The surface must be clean, dry and free of sharp objects. In some cases, a suitable geotextile must be placed.

The membrane should be left for about 30 minutes before carrying out the joints.

Carry out the joint by fitting together the self-adhesive joints of two adjoining sheets. Remove the protection film from both of them and join them (self-adhesive joint with self-adhesive joint), without needing a primer coat.

Finally, press the joint with a roller over the membrane first across and then lengthways.

Please contact the Giscosa Technical Department if you would like any additional information.

4. Performance

The dimensions of the Giscotape membrane will be calculated to cover the surface, including the exposed edges of joints and elevated objects.

5. Characteristics

Tensile strength (MPa)	≥9
Elongation (%)	≥400
Durability (UV)	Pass
Ozone resistance	Pass
Shear resistance	200 N/50 mm
Peeling strength	25 N/50 mm

The Giscotape range has the CE Marking in accordance with standards EN 13956 and EN 13967.

Giscotape sheets comply with different national and international standards. Please contact the Giscosa Technical Department if you would like any additional information.

6. Presentation/Storage/Expiry

Rolls: 1.5 metres wide x 20 metres long.

Other lengths are available upon request.

Protect from mechanical aggressions. Store away from combustion sources and open flames.

Use within 12 months if they are stored properly.

7. Precautions

For more information read the product safety data sheet.