

GISCOLENE PEEL & STICK

1. Description

The Giscolene Peel&Stick membrane is a waterproofing vulcanised EPDM rubber sheet, laminated to a 0.6 mm-thick self-adhesive butyl film.

The membrane adheres perfectly to the surface thanks to the self-adhesive lamination, without needing a primer coat.

2. Properties

- Permanent elasticity from -45°C to 130°C.
- Ozone and UV radiation resistance.
- Excellent thermal and dimensional stability.
- Easy and fast to install.
- No need for a primer coat

3. Application

The waterproofing system with Giscolene Peel&Stick sheets should be installed by experienced personnel and approved installers, in accordance with the Giscosa Technical Manual, and using the system's accessories.

The area to be waterproofed must be in the normal conditions to carry out a waterproofing job. The surface must be clean, dry and free of sharp objects.

The membrane should be left for about 30 minutes before carrying out the joints and fixing it permanently.

Please contact the Giscosa Technical Department if you would like any additional information.

4. Performance

The dimensions of the Giscolene Peel&Stick membrane will be calculated to cover the surface, including the exposed edges of joints and elevated objects.

5. Characteristics

Tensile strength (MPa)	≥9
Elongation (%)	≥400
Hardness (Shore A)	50-70
Durability (UV)	Pass
Ozone resistance	Pass

Please contact the Giscosa Technical Department if you would like any additional information.

6. Presentation/Storage/Expiry

Rolls: 1.0 metre wide x 10 metres long.

Protect from mechanical aggressions. Store away from combustion sources and open flames.

Unlimited expiry.

7. Precautions

For more information read the product safety data sheet.